



MODEL NUMBER

DC-16SL

SPECIFICATIONS

FREQUENCY

868 MHz / 433 MHz

POWER

CR2 3V 850mAh Lithium battery x 1
(pre-inserted)

BATTERY LIFE

11 years*

* Note: Battery life is calculated at an average of 20 activations per day.

OPERATING TEMPERATURE

-10°C to +50°C

OPERATING HUMIDITY

Up to 85% non-condensing

DIMENSIONS

85mm X 24.6mm X 19.5mm

CERTIFICATIONS

CE, EN Grade 2, RCM, MTC, SUBTEL, SIRIM,
IMDA, SIGET, MoC, ARCOTEL, ANATEL



Door/Window Contact Series

- Wireless encrypted F1 Technology with 2km range
- Randomized supervision signals for system integrity checks and troubleshooting
- Tamper protection to prevent unauthorized removal, sabotage, or unsteady installation
- Power magnet allows for an overall side-to-side gap distance of 32mm
- Low battery detection
- Compact and slim design
- Compatible with all Climax panels
- One-way communication with the control panel

DESCRIPTION

The small sized door contact DC-16SL is designed to monitor the opening/closing of windows or door and to alert a user to any irregular activities. With extended life battery and lower power consumption, DC-16SL delivers greater performance and lengthens usage time. Its powerful magnet makes installation more easy and flexible. The slim and small housing allows DC-16SL to blend discretely into any home décor. And, its tamper protection function prevents it from being removed or destroyed by the intruder.

SERVICE PACKAGES

- Commercial
- Commercial Plus
- Interactive
- Interactive + Automation
- Interactive Gold